



Gilian 5000

If it were any tougher it would beat you up and steal your lunch money.

Performance and Reliability

The Gilian 5000 air sampling pump is a rugged and reliable personal air sampling pump that outperforms the competition while working in the harshest conditions. The pump samples up to 5 liters per minute and overcomes high back-pressure that causes other air sampling pumps to fault and stop sampling. It is user-friendly thanks to a four-button keypad and easy menu structure and has an auto-recovery feature that helps save samples after temporary fault conditions lasting up to thirty minutes. The Gilian 5000 is intrinsically safe certified and meets EN1232.

Simply put, the 5000 is the toughest pump on the market.

Feature		Gilian 3500	Gilian 5000				
Flow Rate, Max Flow Rate, with Low Flow Module Flow Rate, Standard		3.5 Liters Per Minute 20 cc/min - 750 cc/min 700 cc/min - 3500 cc/min	5 Liters Per Minute 20 cc/min - 800 cc/min 800 cc/min - 5000 cc/min				
				Flow Compensation	1000 cc/min	30" H ₂ 0 back-pressure (7.5 kPa)	70" H20 back-pressure (17.4 kPa)
					2000 cc/min	30" H ₂ 0 back-pressure (7.5 kPa)	60" H20 back-pressure (15.0 kPa)
	3000 cc/min	20" H ₂ 0 back-pressure (5.0 kPa)	50" H20 back-pressure (12.4 kPa)				
	4000 cc/min	-	30" H20 back-pressure (7.5 kPa)				
	5000 cc/min	-	20" H20 back-pressure (5.0 kPa)				
Constant Flow Control		Better than \pm 3% of set flow (after calibration) between 1-3 LPM; \pm 5% above 3 LPM and below 1LPM	± 5% of set flow at 800-5000 cc/min				
Programmable		No	Yes, four stage				
30-Day Calibration		Yes	Yes				
EN 1232 Compliant		No	Yes				
Live Flow Display		Yes	Yes				
Charging Time		Under 5 Hours	Under 4 Hours				
Memory-Free Battery		Yes, NiMH	Yes, NiMH				
Four-Button User Interface		Yes, with lock-out feature	Yes, with lock-out feature				
Run Time		8 hour minimum	8 hour minimum				
Flow Fault		±5% set flow, fault icon appears; if fault exceeds 30 seconds pump shuts down. Pump will attempt restart every 3 minutes for up to 30 minutes.	±5% set flow, fault icon appears; if fault exceeds 30 seconds pump shuts down. Pump will attempt restart every 3 minutes for up to 30 minutes.				
LCD Display		Yes; Flow Rate, Total Sample Time, Total Volume Sampled, Charge Status.	Yes; Flow Rate, Total Sample Time, Total Volume Sampled, Charge Status , Program Settings.				
Hazardous Approval Ratings		UL: Class I, Division I, Goups A, B, C & D; Class II, Groups E, F & G; Class III, Temp Code T3C cUL: Class I, Division I, Groups C &D Class II, Groups E, F, G; Class III, Temp Code T3C CE: Ex II 2 G, Eex ib IIB T4	FM: Class I, Division I, Groups A, B, C & D Class II, Groups E, F & G Class III, T4 CE: Ex II 1 G, Ex ia IIC T4				